

MF260 - 60HP 2WD



MF 260 Specifications

PERFORMANCE

| | |
|---------------------------------|---------------|
| Engine power at 2,250 rpm | 60 (B.S.) hp* |
| Torque at 1,600 Engine rpm | 212 Nm |
| PTO power at rated engine speed | 48 hp** |

* Certified to BS AU 141a: (1971)

** Manufacturer's estimate

ENGINE

| | |
|-------------------|----------------------|
| Type | Diesel |
| No. of cylinders | 3 |
| Injection | Direct |
| Bore | 91.5 mm |
| Stroke | 127 mm |
| Capacity (litres) | 2.5 |
| Aspiration | Turbo |
| Compression ratio | 15.5:1 |
| Starting aid | Thermostat |
| Throttle control | Hand and foot |
| Cooling | Water |
| Air Cleaner Type | Oil bath |
| Air Pre-Cleaner | Over bonnet |
| Fuel filter | Dual, high capacity |
| Exhaust | Vertical |
| Oil Cooler | Air Cooled, Fin Type |

ELECTRICS

| | |
|---------------|---------------------|
| Voltage | 12V, Negative Earth |
| Battery | 118 Ah |
| Starter motor | 2.2 kW |
| Alternator | 32 Amp. |

CLUTCH

| | |
|----------|------------|
| Type | Dual |
| Diameter | 305x254 mm |

TRANSMISSION

| | | |
|---|----------------------|--|
| Type | Sliding spur | |
| Number of gears | 8 forward, 2 reverse | |
| Road speed at 2,250 engine rpm with 14.9/13-28 rear tyres | | |
| Gear | Speed (km/hr) | |
| Forward 1 (first low) | 2.6 | |
| Forward 2 | 3.8 | |
| Forward 3 | 5.2 | |
| Forward 4 | 7.0 | |
| Forward 5 (first high) | 10.4 | |
| Forward 6 | 15.2 | |
| Forward 7 | 20.8 | |
| Forward 8 | 27.9 | |
| Reverse 1 (low) | 3.5 | |
| Reverse 2 (high) | 14.1 | |

HYDRAULICS

| | |
|---|---|
| Functions | Draft control, Position control, Response Control, Constant pumping |
| Pump Type | Reciprocating Ferguson Pump |
| Oil Flow | 16 l / min |
| Pressure | 21 MPa at normal operating temperature |
| Lift capacity with lower links horizontal | 2,145 kg |
| Lower Links | With Cat. I & II interchangeable balls |

CAPACITIES

| | |
|----------------------|--------|
| Fuel Tank | 47.5 l |
| Engine sump | 6.8 l |
| Cooling system | 10.2 l |
| Hydraulic system | 36.0 l |
| Steering box | 0.9 l |
| Oil bath air cleaner | 0.5 l |

STANDARD EQUIPMENT

Weight frame without weights, Standard tool box with set of tools, Top link, Top link end Cat I & II balls, Check chains, Spring suspension seat, Flat top fenders & Operator's & Service Manual.

OPTIONAL EQUIPMENT

Front end weights, Swinging drawbar, Sun Canopy, Pintle hook and 9 Hole drawbar.

POWER TAKE OFF

| | |
|-----------------------------|-----------|
| Type | Live |
| Engine speed at 540 PTO rpm | 1,789 rpm |
| Shaft diameter | 35 mm |
| No. of splines | 6 |

FRONT AXLE

| | |
|----------|-------------------------|
| Type | Box Section, Adjustable |
| Steering | Manual |

REAR AXLE AND BRAKES

| | |
|------------------|--|
| Axle Type | Straddle with epicyclic reduction unit |
| Brake Type | Oil immersed, multi-disc |
| Brakes Actuation | Mechanical |
| Parking Brake | Hand Lever Operated |

INSTRUMENTATION

| | |
|----------------|--|
| Gauges | Tachometer, Hourmeter, Fuel level, Battery condition & Water temperature |
| Warning lights | Direction indicators, Electric charge, Headlight main beam, Low engine oil pressure, Brake lights & Auxiliary socket |

TYRES

| | |
|-------|-------------------|
| Front | 7.50-16 (6PR) |
| Rear | 14.9/13-28 (6 PR) |

TRACK ADJUSTMENT

| | |
|-------|----------------|
| Front | 1,245-1,854 mm |
| Rear | 1,423-2,134 mm |

WEIGHT AND DIMENSIONS (Approx.)

(With 7.50-16 front and 14.9/13-28 rear wheel and with full fuel, oil and water)

| | |
|----------------------|----------|
| Weight | |
| Gross Weight | 1,900 kg |
| Dimensions | |
| Wheel base | 1,892 mm |
| Overall length | 3,260 mm |
| Overall width (min.) | 1,890 mm |
| Height | |
| Over Exhaust | 2,220 mm |
| Over Steering Wheel | 1,490 mm |
| Turning circle | |
| With brakes | 5,840 mm |
| Without brakes | 6,580 mm |
| Ground clearance | |
| Under gear box | 400 mm |



+92-42-37919510

sales@faizantraders.com

www.faizantraders.com